



Обработка отверстий

beyond

НОВИНКА!

## ■ B272Z\_HPG/HPS • 20 x D



- лучший выбор
- альтернативный выбор

КРРК20	KN25	диаметр D1				L	L3	L4 max	L5	LS	D
		мм	дюйм	значение	диаметр проволоки						
B272Z02383KMG	B272Z02383KMS	2,383	.0938	3/32	—	101	63	56	0,5	30	3
B272Z02400KMG	B272Z02400KMS	2,400	.0945	—	—	101	63	56	0,5	30	3
—	B272Z02439KMS	2,439	.0960	—	41	101	63	56	0,5	30	3
B272Z02489KMG	B272Z02489KMS	2,489	.0980	—	40	101	63	56	0,5	30	3
B272Z02500KMG	B272Z02500KMS	2,500	.0984	—	—	101	63	56	0,5	30	3
—	B272Z02578KMS	2,578	.1015	—	38	101	64	57	0,5	30	3
B272Z02600KMG	B272Z02600KMS	2,600	.1024	—	—	101	64	57	0,5	30	3
B272Z02642KMG	B272Z02642KMS	2,642	.1040	—	37	101	65	58	0,5	30	3
B272Z02705KMG	B272Z02705KMS	2,705	.1065	—	36	101	65	58	0,5	30	3
B272Z02779KMG	B272Z02779KMS	2,779	.1094	7/64	—	101	66	59	0,6	30	3
—	B272Z02800KMS	2,800	.1102	—	—	101	66	59	0,6	30	3
—	B272Z02820KMS	2,820	.1110	—	34	101	66	59	0,6	30	3
—	B272Z02870KMS	2,870	.1130	—	33	101	66	59	0,6	30	3
—	B272Z02900KMS	2,900	.1142	—	—	101	67	60	0,6	30	3
B272Z02947KMG	B272Z02947KMS	2,947	.1160	—	32	101	67	60	0,6	30	3
B272Z03000HPG	B272Z03000HPS	3,000	.1181	—	—	101	67	60	0,6	30	3
B272Z03175HPG	B272Z03175HPS	3,175	.1250	1/8	—	125	83	74	0,6	32	4
B272Z03300HPG	B272Z03300HPS	3,300	.1299	—	—	125	84	75	0,6	32	4
B272Z03500HPG	B272Z03500HPS	3,500	.1378	—	—	125	86	77	0,6	32	4
B272Z03850HPG	—	3,850	.1516	—	—	125	88	79	0,7	32	4
B272Z03970HPG	B272Z03970HPS	3,970	.1563	5/32	—	125	89	79	0,7	32	4
B272Z04000HPG	B272Z04000HPS	4,000	.1575	—	—	125	90	80	0,7	32	4
B272Z04500HPG	B272Z04500HPS	4,500	.1772	—	—	149	108	97	0,8	34	5
B272Z04623HPG	—	4,623	.1820	—	14	149	109	98	0,9	34	5
B272Z04763HPG	B272Z04763HPS	4,763	.1875	3/16	—	149	110	99	0,9	34	5
B272Z05000HPG	B272Z05000HPS	5,000	.1969	—	—	149	112	100	0,9	34	5
B272Z05200HPG	—	5,200	.2047	—	—	173	127	114	1,0	36	6
B272Z05260HPG	—	5,260	.2071	—	—	173	128	115	1,0	36	6

(продолжение)