



Значения размеров L, L3 и L4 max приведены в таблице на стр. B51.



beyond

■ B284/B285_HPS • ~3 x D/~5 x D



- лучший выбор
- альтернативный выбор

укороченное • KN15	удлиненное • KN15	диаметр D1			диаметр проволоки	L5	LS	D
		мм	дюйм	значение				
B284D03000HPS	B285D03000HPS	3,000	.1181	—	—	0,6	36	6
B284D03175HPS	B285D03175HPS	3,175	.1250	1/8	—	0,6	36	6
B284D03200HPS	B285D03200HPS	3,200	.1260	—	—	0,6	36	6
B284D03300HPS	B285D03300HPS	3,300	.1299	—	—	0,6	36	6
B284D03500HPS	—	3,500	.1378	—	—	0,6	36	6
B284D03571HPS	—	3,571	.1406	9/64	—	0,7	36	6
B284D03970HPS	B285D03970HPS	3,970	.1563	5/32	—	0,7	36	6
B284D04000HPS	B285D04000HPS	4,000	.1575	—	—	0,7	36	6
B284D04200HPS	B285D04200HPS	4,200	.1654	—	—	0,8	36	6
B284D04366HPS	—	4,366	.1719	11/64	—	0,8	36	6
B284D04500HPS	B285D04500HPS	4,500	.1772	—	—	0,8	36	6
B284D04763HPS	B285D04763HPS	4,763	.1875	3/16	—	0,9	36	6
B284D04800HPS	B285D04800HPS	4,800	.1890	—	12	0,9	36	6
—	B285D04900HPS	4,900	.1929	—	—	0,9	36	6
B284D05000HPS	B285D05000HPS	5,000	.1969	—	—	0,9	36	6
B284D05100HPS	B285D05100HPS	5,100	.2008	—	—	0,9	36	6
B284D05159HPS	—	5,159	.2031	13/64	—	1,0	36	6
—	B285D05200HPS	5,200	.2047	—	—	1,0	36	6
—	B285D05500HPS	5,500	.2165	—	—	1,0	36	6
B284D05558HPS	B285D05558HPS	5,558	.2188	7/32	—	1,0	36	6
B284D05600HPS	B285D05600HPS	5,600	.2205	—	—	1,0	36	6
B284D05800HPS	—	5,800	.2283	—	—	1,1	36	6
B284D05954HPS	—	5,954	.2344	15/64	—	1,1	36	6
B284D06000HPS	B285D06000HPS	6,000	.2362	—	—	1,1	36	6
—	B285D06300HPS	6,300	.2480	—	—	1,2	36	8
B284D06400HPS	B285D06400HPS	6,400	.2520	—	—	1,2	36	8
B284D06500HPS	B285D06500HPS	6,500	.2559	—	—	1,2	36	8
—	B285D06600HPS	6,600	.2598	—	—	1,2	36	8
—	B285D06700HPS	6,700	.2638	—	—	1,2	36	8
B284D06746HPS	—	6,746	.2656	17/64	—	1,2	36	8
B284D06800HPS	—	6,800	.2677	—	—	1,3	36	8
B284D07000HPS	B285D07000HPS	7,000	.2756	—	—	1,3	36	8

(продолжение)