



(B284/B285_HPS • 3 x D/5 x D — продолжение)



- лучший выбор
○ альтернативный выбор

		диаметр D1						
укороченное • KN15	удлиненное • KN15	мм	дюйм	значение	диаметр проволоки	L5	LS	D
B284D07145HPS	B285D07145HPS	7,145	.2813	9/32	—	1,3	36	8
B284D07400HPS	B285D07400HPS	7,400	.2913	—	—	1,4	36	8
B284D07500HPS	—	7,500	.2953	—	—	1,4	36	8
B284D07541HPS	—	7,541	.2969	19/64	—	1,4	36	8
—	B285D07700HPS	7,700	.3031	—	—	1,4	36	8
—	B285D07800HPS	7,800	.3071	—	—	1,4	36	8
B284D07938HPS	B285D07938HPS	7,938	.3125	5/16	—	1,5	36	8
B284D08000HPS	—	8,000	.3150	—	—	1,5	36	8
B284D08334HPS	B285D08334HPS	8,334	.3281	21/64	—	1,5	40	10
—	B285D08400HPS	8,400	.3307	—	—	1,6	40	10
B284D08500HPS	B285D08500HPS	8,500	.3346	—	—	1,6	40	10
B284D08733HPS	B285D08733HPS	8,733	.3438	11/32	—	1,6	40	10
B284D09000HPS	B285D09000HPS	9,000	.3543	—	—	1,7	40	10
B284D09129HPS	—	9,129	.3594	23/64	—	1,7	40	10
—	B285D09300HPS	9,300	.3661	—	—	1,7	40	10
B284D09500HPS	B285D09500HPS	9,500	.3740	—	—	1,8	40	10
B284D09525HPS	B285D09525HPS	9,525	.3750	3/8	—	1,8	40	10
B284D09921HPS	—	9,921	.3906	25/64	—	1,8	40	10
B284D10000HPS	B285D10000HPS	10,000	.3937	—	—	1,8	40	10
B284D10200HPS	—	10,200	.4016	—	—	1,9	45	12
B284D10320HPS	—	10,320	.4063	13/32	—	1,9	45	12
B284D10500HPS	B285D10500HPS	10,500	.4134	—	—	1,9	45	12
B284D10716HPS	—	10,716	.4219	27/64	—	2,0	45	12
B284D11000HPS	B285D11000HPS	11,000	.4331	—	—	2,0	45	12
B284D11113HPS	B285D11113HPS	11,113	.4375	7/16	—	2,1	45	12
—	B285D11500HPS	11,500	.4528	—	—	2,1	45	12
B284D11908HPS	—	11,908	.4688	15/32	—	2,2	45	12
B284D12000HPS	B285D12000HPS	12,000	.4724	—	—	2,2	45	12
B284D12500HPS	—	12,500	.4921	—	—	2,3	45	14
B284D12700HPS	—	12,700	.5000	1/2	—	2,3	45	14
B284D14000HPS	B285D14000HPS	14,000	.5512	—	—	2,6	45	14
B284D14288HPS	—	14,288	.5625	9/16	—	2,6	48	16
—	B285D14500HPS	14,500	.5709	—	—	2,7	48	16
B284D15875HPS	—	15,875	.6250	5/8	—	2,9	48	16
—	B285D18000HPS	18,000	.7087	—	—	3,3	48	18
B284D19050HPS	—	19,050	.7500	3/4	—	3,5	50	20
B284D20000HPS	—	20,000	.7874	—	—	3,7	50	20

Точность изготовления • Метрическая система

номинальный диапазон размеров	D1 допуск m7	D допуск h6
>3–6	0,004/0,016	0,000/-0,008
>6–10	0,006/0,021	0,000/-0,009
>10–18	0,007/0,025	0,000/-0,011
>18–25,4	0,008/0,029	0,000/-0,013