



Product			Dimensions (mm)				
EDP	Item Description	Grade	d (IC)	l	s	r	hm min
012499	TPKN1603PDTR	MP91M	9,52	16,50	3,18	Facet	0,05
034681	TPKN1603PDTR	SP6519	9,52	16,50	3,18	Facet	0,05
012501	TPKN2204PDTR	MP91M	12,70	22,00	4,76	Facet	0,05
034682	TPKN2204PDTR	SP6519	12,70	22,00	4,76	Facet	0,05



**TPKN\_**

As pressed circumference  $\chi$  60° with ground face and without chip-breaker

024947	TPMT110204E-M	X500	6,35	11,00	2,38	0,40	0,03
--------	---------------	------	------	-------	------	------	------



**TPMT\_-M**

As pressed circumference one face pressed chip-breaker  $\chi$  45° and  $\chi$  60°.

012503	TPUN220408E	MP91M	12,70	22,00	4,76	0,80	0,05
--------	-------------	-------	-------	-------	------	------	------



**TPUN\_**

As pressed circumference without chip-breaker

033067	XDLT090408ER-D41	SC6525	9,52	9,52	4,76	0,80	0,05
031535	XDLT090408ER-D41	SP6519	9,52	9,52	4,76	0,80	0,05
029685	XDLT090408ER-D41	X500	9,52	9,52	4,76	0,80	0,05
033068	XDLT120508ER-D41	SC6525	12,70	12,70	5,56	0,80	0,05
031534	XDLT120508ER-D41	SP6519	12,70	12,70	5,56	0,80	0,05
029682	XDLT120508ER-D41	X500	12,70	12,70	5,56	0,80	0,05



**XDLT\_-D41**

Ground circumference one face pressed chip-breaker

030854	XDLT090412ER-D411	SP6519	9,52	9,52	4,76	1,20	0,05
030853	XDLT090412ER-D411	X500	9,52	9,52	4,76	1,20	0,05
030792	XDLT120512ER-D411	SP6519	12,70	12,70	5,56	1,20	0,05
030783	XDLT120512ER-D411	X500	12,70	12,70	5,56	1,20	0,05



**XDLT\_-D411**

Ground circumference one face pressed chip-breaker

029637	XDLT090408ER-D721	GH2	9,52	9,52	4,76	0,80	0,03
029638	XDLT120508ER-D721	GH2	12,70	12,70	5,56	0,80	0,03



**XDLT\_-D721**

Ground circumference one face pressed chip-breaker

029486	XDLW090408SR-D	SC3025	9,52	9,52	4,76	0,80	0,25
029487	XDLW090408SR-D	X400	9,52	9,52	4,76	0,80	0,25
029485	XDLW090408SR-D	X500	9,52	9,52	4,76	0,80	0,25
029489	XDLW120508SR-D	SC3025	12,70	12,70	5,56	0,80	0,30
029490	XDLW120508SR-D	X400	12,70	12,70	5,56	0,80	0,30
029488	XDLW120508SR-D	X500	12,70	12,70	5,56	0,80	0,30



**XDLW\_-D**

Ground circumference without chip-breaker

033069	XELT160512ER-D41	SC6525	16,80	16,80	5,56	1,20	0,10
031294	XELT160512ER-D41	SP6519	16,80	16,80	5,56	1,20	0,10
031293	XELT160512ER-D41	X500	16,80	16,80	5,56	1,20	0,10



**XELT\_-D41**

Ground circumference one face pressed chip-breaker

031292	XELW160512SR-D	SC3025	16,80	16,80	5,56	1,20	0,30
031291	XELW160512SR-D	X400	16,80	16,80	5,56	1,20	0,30



**XELW\_-D**

Ground circumference without chip-breaker