






■ Рекомендации по применению • Максимальная частота вращения

	Обрабатываемый диаметр				Максимальное число оборотов	
	D1		D1			
	min (мм)	max (мм)	min (дюйм)	max (дюйм)		
ModBORE™ RBHT 	24	31	0.9449	1.2205	12000	
	31	40	1.2205	1.5748	10000	
	40	51	1.5748	2.0079	8000	
	51	67	2.0079	2.6378	6500	
	67	87	2.6378	3.4252	5000	
	87	116	3.4252	4.5669	4000	
	116	153	4.5669	6.0236	3000	
ModBORE FBHS 	24	31	0.9449	1.2205	с балансировкой	без балансировки
	31	40	1.2205	1.5748	12000	9000
	40	51	1.5748	2.0079	10000	7500
	51	67	2.0079	2.6378	8000	5250
	67	87	2.6378	3.4252	6500	4000
	87	116	3.4252	4.5669	5000	3000
	116	171	4.5669	6.7323	4000	2500
ModBORE FBHO 	3	20	0.1181	0.7874	расточная головка со смещением	
	20	48	0.7874	1.8898	max 0,5 мм (.02")	0,5–2,5 мм (.02–.1")
	48	88	1.8898	3.4646	16000	6000
ModBORE FBHM 	3	20	0.1181	0.7874	расточная головка со смещением	
	20	48	0.7874	1.8898	max 0,5 мм (.02")	0,5–2,5 мм (.02–.1")
	48	88	1.8898	3.4646	16000	6000
	86	164	3.3858	6.4567	12000	4000
	164	320	6.4567	12.5984	8000	2000
	—	—	0.0000	0.0000	1000	—
	—	—	0.0000	0.0000	500	—
Ползуны мостового типа ModBORE 	150	205	5.9055	8.0709	1250	
	200	255	7.8740	10.0394	1000	
	250	305	9.8425	12.0079	850	
	300	355	11.8110	13.9764	700	
	350	405	13.7795	15.9449	600	
	400	455	15.7480	17.9134	530	
	450	505	17.7165	19.8819	480	
	500	555	19.6850	21.8504	440	
550	605	21.6535	23.8189	400		
600	655	23.6220	25.7874	380		



Инструменты для чистовой обработки отверстий