




(B051A/B052A/B053A • ~3 x D/~5 x D/~8 x D, продолжение)



укороченное • KC7325



удлинненное • KC7325



сверхдлинное • KC7325

			диаметр D1						
			мм	дюйм	значение	диаметр проволоки	L5	LS	D
B051A1000CPG	B052A1000CPG	B053A1000CPG	10,000	.3937	—	—	1,7	40	10
B051A10100CPG	B052A10100CPG	B053A10100CPG	10,100	.3976	—	—	1,7	45	12
B051A10200CPG	B052A10200CPG	B053A10200CPG	10,200	.4016	—	—	1,7	45	12
B051A10300CPG	B052A10300CPG	B053A10300CPG	10,300	.4055	—	—	1,8	45	12
B051A10320CPG	B052A10320CPG	B053A10320CPG	10,320	.4063	13/32	—	1,8	45	12
B051A10400CPG	B052A10400CPG	B053A10400CPG	10,400	.4094	—	—	1,8	45	12
B051A10500CPG	B052A10500CPG	B053A10500CPG	10,500	.4134	—	—	1,8	45	12
B051A10600CPG	B052A10600CPG	B053A10600CPG	10,600	.4173	—	—	1,8	45	12
B051A10700CPG	B052A10700CPG	B053A10700CPG	10,700	.4213	—	—	1,8	45	12
B051A10716CPG	B052A10716CPG	B053A10716CPG	10,716	.4219	27/64	—	1,8	45	12
B051A10800CPG	B052A10800CPG	B053A10800CPG	10,800	.4252	—	—	1,8	45	12
B051A10900CPG	B052A10900CPG	B053A10900CPG	10,900	.4291	—	—	1,9	45	12
B051A11000CPG	B052A11000CPG	B053A11000CPG	11,000	.4331	—	—	1,9	45	12
B051A11100CPG	B052A11100CPG	B053A11100CPG	11,100	.4370	—	—	1,9	45	12
B051A11113CPG	B052A11113CPG	B053A11113CPG	11,113	.4375	7/16	—	1,9	45	12
B051A11200CPG	B052A11200CPG	B053A11200CPG	11,200	.4409	—	—	1,9	45	12
B051A11300CPG	B052A11300CPG	B053A11300CPG	11,300	.4449	—	—	1,9	45	12
B051A11400CPG	B052A11400CPG	B053A11400CPG	11,400	.4488	—	—	2,0	45	12
B051A11500CPG	B052A11500CPG	B053A11500CPG	11,500	.4528	—	—	2,0	45	12
B051A11509CPG	B052A11509CPG	B053A11509CPG	11,509	.4531	29/64	—	2,0	45	12
B051A11600CPG	B052A11600CPG	B053A11600CPG	11,600	.4567	—	—	2,0	45	12
B051A11700CPG	B052A11700CPG	B053A11700CPG	11,700	.4606	—	—	2,0	45	12
B051A11800CPG	B052A11800CPG	B053A11800CPG	11,800	.4646	—	—	2,0	45	12
B051A11900CPG	B052A11900CPG	B053A11900CPG	11,900	.4685	—	—	2,0	45	12
B051A11908CPG	B052A11908CPG	B053A11908CPG	11,908	.4688	15/32	—	2,0	45	12
B051A12000CPG	B052A12000CPG	B053A12000CPG	12,000	.4724	—	—	2,1	45	12
B051A12100CPG	B052A12100CPG	B053A12100CPG	12,100	.4764	—	—	2,1	45	14
B051A12200CPG	B052A12200CPG	B053A12200CPG	12,200	.4803	—	—	2,1	45	14
B051A12300CPG	B052A12300CPG	B053A12300CPG	12,300	.4843	—	—	2,1	45	14
B051A12304CPG	B052A12304CPG	B053A12304CPG	12,304	.4844	31/64	—	2,1	45	14
B051A12400CPG	B052A12400CPG	B053A12400CPG	12,400	.4882	—	—	2,1	45	14
B051A12500CPG	B052A12500CPG	B053A12500CPG	12,500	.4921	—	—	2,1	45	14
B051A12600CPG	B052A12600CPG	B053A12600CPG	12,600	.4961	—	—	2,2	45	14
B051A12700CPG	B052A12700CPG	B053A12700CPG	12,700	.5000	1/2	—	2,2	45	14

Цельные твердосплавные сверла

Точность изготовления • Метрическая система

диапазон номинальных размеров	D1 допуск	D допуск h6
1-3	0,000/-0,014 (h8)	0,000/-0,006
>3-6	0,000/-0,012 (h7)	0,000/-0,008
>6-10	0,000/-0,015 (h7)	0,000/-0,009
>10-18	0,000/-0,018 (h7)	0,000/-0,011
>18-20	0,000/-0,021 (h7)	0,000/-0,013