



(B105 • ~5 x D, продолжение)



		диаметр D1			диаметр проволоки	L	L4 max	L5	LS	D
		мм	дюйм	значение						
<b>K10</b>	<b>KC7210</b>									
B105A08700	—	8,700	.3425	—	—	103	49	2,2	40	10
B105A08800	—	8,800	.3465	—	—	103	49	2,2	40	10
B105A09000	<b>B105A09000</b>	9,000	.3543	—	—	103	49	2,2	40	10
B105A09100	—	9,100	.3583	—	—	103	49	2,3	40	10
B105A09300	—	9,300	.3661	—	—	103	49	2,3	40	10
B105A09500	—	9,500	.3740	—	—	103	49	2,4	40	10
B105A09700	—	9,700	.3819	—	—	103	49	2,4	40	10
B105A09800	—	9,800	.3858	—	—	103	49	2,4	40	10
B105A10000	<b>B105A10000</b>	10,000	.3937	—	—	103	49	2,5	40	10
B105A10100	—	10,100	.3976	—	—	118	56	2,5	45	12
B105A10200	<b>B105A10200</b>	10,200	.4016	—	—	118	56	2,5	45	12
B105A10300	—	10,300	.4055	—	—	118	56	2,6	45	12
B105A10500	<b>B105A10500</b>	10,500	.4134	—	—	118	56	2,6	45	12
B105A10700	—	10,700	.4213	—	—	118	56	2,7	45	12
B105A10800	—	10,800	.4252	—	—	118	56	2,7	45	12
B105A11000	<b>B105A11000</b>	11,000	.4331	—	—	118	56	2,7	45	12
B105A11100	—	11,100	.4370	—	—	118	56	2,8	45	12
B105A11200	—	11,200	.4409	—	—	118	56	2,8	45	12
B105A11500	<b>B105A11500</b>	11,500	.4528	—	—	118	56	2,9	45	12
B105A11700	—	11,700	.4606	—	—	118	56	2,9	45	12
B105A11800	—	11,800	.4646	—	—	118	56	2,9	45	12
B105A12000	<b>B105A12000</b>	12,000	.4724	—	—	118	56	3,0	45	12
B105A12100	—	12,100	.4764	—	—	124	60	3,0	45	14
B105A12500	<b>B105A12500</b>	12,500	.4921	—	—	124	60	3,1	45	14
B105A12700	—	12,700	.5000	1/2	—	124	60	3,2	45	14
B105A12800	—	12,800	.5039	—	—	124	60	3,2	45	14
B105A13000	<b>B105A13000</b>	13,000	.5118	—	—	124	60	3,2	45	14
B105A13100	—	13,100	.5157	—	—	124	60	3,3	45	14
B105A13500	<b>B105A13500</b>	13,500	.5315	—	—	124	60	3,4	45	14
B105A13800	—	13,800	.5433	—	—	124	60	3,4	45	14
B105A14000	<b>B105A14000</b>	14,000	.5512	—	—	124	60	3,5	45	14
B105A14200	—	14,200	.5591	—	—	133	63	3,5	48	16
B105A14500	—	14,500	.5709	—	—	133	63	3,6	48	16
B105A15000	<b>B105A15000</b>	15,000	.5906	—	—	133	63	3,7	48	16
B105A15100	—	15,100	.5945	—	—	133	63	3,8	48	16
B105A15500	<b>B105A15500</b>	15,500	.6102	—	—	133	63	3,9	48	16
B105A15800	—	15,800	.6220	—	—	133	63	3,9	48	16
B105A16000	—	16,000	.6299	—	—	133	63	4,0	48	16
B105A16500	—	16,500	.6496	—	—	143	71	4,1	48	18
B105A17000	—	17,000	.6693	—	—	143	71	4,2	48	18
B105A17500	<b>B105A17500</b>	17,500	.6890	—	—	143	71	4,4	48	18
B105A18000	<b>B105A18000</b>	18,000	.7087	—	—	143	71	4,5	48	18
B105A18500	<b>B105A18500</b>	18,500	.7283	—	—	153	77	4,6	50	20
B105A19000	—	19,000	.7480	—	—	153	77	4,7	50	20
B105A19500	—	19,500	.7677	—	—	153	77	4,9	50	20
B105A20000	—	20,000	.7874	—	—	153	77	5,0	50	20
B105A20500	—	20,500	.8071	—	—	167	85	5,1	50	20
B105A21000	—	21,000	.8268	—	—	167	85	5,2	50	20

Точность изготовления • Метрическая система

диапазон номинальных размеров	D1 допуск m7	D допуск h6
>3-6	0,004/0,016	0,000/-0,008
>6-10	0,006/0,021	0,000/-0,009
>10-18	0,007/0,025	0,000/-0,011
>18-25,4	0,008/0,029	0,000/-0,013