




(B210/B211/B212_HP • ~3 x D/~5 x D/~8 x D, продолжение)



укороченное • KCM15



удлиненное • KCM15



сверхдлинное • KCM15

			диаметр D1			диаметр проволоки	L5	LS	D
			мм	дюйм	значение				
—	B211A15300HP	—	15,300	.6024	—	—	2,8	48	16
—	B211A15400HP	—	15,400	.6063	—	—	2,9	48	16
B210A15500HP	B211A15500HP	—	15,500	.6102	—	—	2,9	48	16
—	B211A15600HP	—	15,600	.6142	—	—	2,9	48	16
—	B211A15700HP	—	15,700	.6181	—	—	2,9	48	16
—	B211A15800HP	—	15,800	.6220	—	—	2,9	48	16
B210A15875HP	B211A15875HP	B212A15875HP	15,875	.6250	5/8	—	3,0	48	16
—	B211A15900HP	—	15,900	.6260	—	—	3,0	48	16
B210A16000HP	B211A16000HP	B212A16000HP	16,000	.6299	—	—	3,0	48	16
—	B211A16100HP	—	16,100	.6339	—	—	3,0	48	18
B210A16500HP	B211A16500HP	—	16,500	.6496	—	—	3,1	48	18
B210A16670HP	—	—	16,670	.6563	21/32	—	3,1	48	18
B210A17000HP	B211A17000HP	—	17,000	.6693	—	—	3,2	48	18
B210A17500HP	B211A17500HP	—	17,500	.6890	—	—	3,3	48	18
—	B211A17700HP	—	17,700	.6969	—	—	3,3	48	18
B210A18000HP	B211A18000HP	—	18,000	.7087	—	—	3,3	48	18
—	B211A18400HP	—	18,400	.7244	—	—	3,4	50	20
B210A18500HP	B211A18500HP	—	18,500	.7283	—	—	3,4	50	20
B210A19000HP	B211A19000HP	—	19,000	.7480	—	—	3,5	50	20
B210A19050HP	B211A19050HP	B212A19050HP	19,050	.7500	3/4	—	3,5	50	20
—	B211A19100HP	—	19,100	.7520	—	—	3,5	50	20
—	B211A19200HP	—	19,200	.7559	—	—	3,6	50	20
—	B211A19300HP	—	19,300	.7598	—	—	3,6	50	20
B210A19500HP	B211A19500HP	—	19,500	.7677	—	—	3,6	50	20
B210A20000HP	B211A20000HP	—	20,000	.7874	—	—	3,7	50	20
—	B211A20500HP	—	20,500	.8071	—	—	3,8	50	20
—	B211A21000HP	—	21,000	.8268	—	—	3,9	50	20

Цельные твердосплавные сверла

Точность изготовления • Метрическая система

диапазон номинальных размеров	D1 допуск m7	D допуск h6
>3-6	0,004/0,016	0,000/-0,008
>6-10	0,006/0,021	0,000/-0,009
>10-18	0,007/0,025	0,000/-0,011
>18-25,4	0,008/0,029	0,000/-0,013