



(B221/B222_HP • ~3 x D/~5 x D, продолжение)

Цельные твердосплавные сверла



укороченное • КСРК15



удлинненное • КСРК15

		диаметр D1						
		мм	дюйм	значение	диаметр проволоки	L5	LS	D
B221A13300HP	—	13,300	.5236	—	—	2,5	45	14
B221A13500HP	B222A13500HP	13,500	.5315	—	—	2,5	45	14
B221A13600HP	—	13,600	.5354	—	—	2,5	45	14
B221A13700HP	—	13,700	.5394	—	—	2,6	45	14
B221A13800HP	—	13,800	.5433	—	—	2,6	45	14
B221A13891HP	—	13,891	.5469	35/64	—	2,6	45	14
B221A13900HP	—	13,900	.5472	—	—	2,6	45	14
B221A14000HP	B222A14000HP	14,000	.5512	—	—	2,6	45	14
B221A14100HP	—	14,100	.5551	—	—	2,6	48	16
B221A14200HP	—	14,200	.5591	—	—	2,6	48	16
B221A14288HP	B222A14288HP	14,288	.5625	9/16	—	2,7	48	16
B221A14300HP	—	14,300	.5630	—	—	2,7	48	16
B221A14400HP	—	14,400	.5669	—	—	2,7	48	16
B221A14500HP	B222A14500HP	14,500	.5709	—	—	2,7	48	16
B221A14600HP	—	14,600	.5748	—	—	2,7	48	16
B221A14684HP	—	14,684	.5781	37/64	—	2,7	48	16
B221A14700HP	—	14,700	.5787	—	—	2,7	48	16
B221A14800HP	—	14,800	.5827	—	—	2,8	48	16
B221A14900HP	—	14,900	.5866	—	—	2,8	48	16
B221A15000HP	B222A15000HP	15,000	.5906	—	—	2,8	48	16
B221A15083HP	—	15,083	.5938	19/32	—	2,8	48	16
B221A15100HP	—	15,100	.5945	—	—	2,8	48	16
B221A15200HP	—	15,200	.5984	—	—	2,8	48	16
B221A15300HP	—	15,300	.6024	—	—	2,8	48	16
B221A15400HP	—	15,400	.6063	—	—	2,9	48	16
B221A15479HP	—	15,479	.6094	39/64	—	2,9	48	16
B221A15500HP	B222A15500HP	15,500	.6102	—	—	2,9	48	16
B221A15600HP	—	15,600	.6142	—	—	2,9	48	16
B221A15700HP	—	15,700	.6181	—	—	2,9	48	16
B221A15800HP	—	15,800	.6220	—	—	2,9	48	16
B221A15875HP	B222A15875HP	15,875	.6250	5/8	—	3,0	48	16
B221A15900HP	—	15,900	.6260	—	—	3,0	48	16
B221A16000HP	B222A16000HP	16,000	.6299	—	—	3,0	48	16
B221A16500HP	B222A16500HP	16,500	.6496	—	—	3,1	48	18
B221A17000HP	B222A17000HP	17,000	.6693	—	—	3,2	48	18
B221A17463HP	B222A17463HP	17,463	.6875	11/16	—	3,2	48	18
B221A17500HP	B222A17500HP	17,500	.6890	—	—	3,3	48	18
B221A17700HP	—	17,700	.6969	—	—	3,3	48	18
B221A18000HP	B222A18000HP	18,000	.7087	—	—	3,3	48	18
B221A18500HP	B222A18500HP	18,500	.7283	—	—	3,4	50	20
B221A19000HP	B222A19000HP	19,000	.7480	—	—	3,5	50	20
B221A19050HP	B222A19050HP	19,050	.7500	3/4	—	3,5	50	20
B221A19500HP	—	19,500	.7677	—	—	3,6	50	20
B221A20000HP	B222A20000HP	20,000	.7874	—	—	3,7	50	20
B221A20500HP	—	20,500	.8071	—	—	3,8	50	20
B221A21000HP	—	21,000	.8268	—	—	3,9	50	20

Точность изготовления • Метрическая система

диапазон номинальных размеров	D1 допуск m7	D допуск h6
>3-6	0,004/0,016	0,000/-0,008
>6-10	0,006/0,021	0,000/-0,009
>10-18	0,007/0,025	0,000/-0,011
>18-25,4	0,008/0,029	0,000/-0,013