



Сведения о L, L3 и L4 max приведены в таблице на вкладке «Цельные твердосплавные сверла».



■ B224/B225_HP • ~3 x D/~5 x D



укороченное • КСРК15



удлинненное • КСРК15

- лучший выбор
- альтернативный выбор

		диаметр D1						
		мм	дюйм	значение	диаметр проволоки	L5	LS	D
B224A03000HP	B225A03000HP	3,000	.1181	—	—	0,6	36	6
B224A03048HP	B225A03048HP	3,048	.1200	—	31	0,6	36	6
B224A03100HP	B225A03100HP	3,100	.1220	—	—	0,6	36	6
B224A03175HP	B225A03175HP	3,175	.1250	1/8	—	0,6	36	6
B224A03200HP	B225A03200HP	3,200	.1260	—	—	0,6	36	6
B224A03264HP	B225A03264HP	3,264	.1285	—	30	0,6	36	6
B224A03300HP	B225A03300HP	3,300	.1299	—	—	0,6	36	6
B224A03400HP	B225A03400HP	3,400	.1339	—	—	0,6	36	6
B224A03455HP	B225A03455HP	3,455	.1360	—	29	0,7	36	6
B224A03500HP	B225A03500HP	3,500	.1378	—	—	0,7	36	6
B224A03571HP	B225A03571HP	3,571	.1406	9/64	—	0,7	36	6
B224A03600HP	B225A03600HP	3,600	.1417	—	—	0,7	36	6
B224A03658HP	—	3,658	.1440	—	27	0,7	36	6
B224A03700HP	B225A03700HP	3,700	.1457	—	—	0,7	36	6
B224A03734HP	—	3,734	.1470	—	26	0,7	36	6
B224A03797HP	B225A03797HP	3,797	.1495	—	25	0,7	36	6
B224A03800HP	B225A03800HP	3,800	.1496	—	—	0,7	36	6
B224A03900HP	B225A03900HP	3,900	.1535	—	—	0,7	36	6
B224A03970HP	B225A03970HP	3,970	.1563	5/32	—	0,7	36	6
B224A04000HP	B225A04000HP	4,000	.1575	—	—	0,8	36	6
B224A04039HP	—	4,039	.1590	—	21	0,8	36	6
B224A04090HP	—	4,090	.1610	—	20	0,8	36	6
—	B225A04100HP	4,100	.1614	—	—	0,8	36	6
B224A04200HP	B225A04200HP	4,200	.1654	—	—	0,8	36	6
B224A04217HP	—	4,217	.1660	—	19	0,8	36	6
—	B225A04300HP	4,300	.1693	—	—	0,8	36	6
B224A04366HP	B225A04366HP	4,366	.1719	11/64	—	0,8	36	6
—	B225A04400HP	4,400	.1732	—	—	0,8	36	6
B224A04496HP	B225A04496HP	4,496	.1770	—	16	0,8	36	6
—	B225A04500HP	4,500	.1772	—	—	0,8	36	6
—	B225A04600HP	4,600	.1811	—	—	0,9	36	6
B224A04623HP	—	4,623	.1820	—	14	0,9	36	6
B224A04700HP	B225A04700HP	4,700	.1850	—	13	0,9	36	6
—	B225A04760HP	4,760	.1874	—	—	0,9	36	6
B224A04763HP	—	4,763	.1875	3/16	—	0,9	36	6
—	B225A04800HP	4,800	.1890	—	12	0,9	36	6
B224A04852HP	—	4,852	.1910	—	11	0,9	36	6
—	B225A04900HP	4,900	.1929	—	—	0,9	36	6
B224A05000HP	B225A05000HP	5,000	.1969	—	—	0,9	36	6
B224A05100HP	B225A05100HP	5,100	.2008	—	—	1,0	36	6

(продолжение)