


Цельные твердосплавные сверла

Сверла HP Beyond™ • Сталь • Внутренний подвод СОЖ




(B224/B225_HP • ~3 x D/~5 x D, продолжение)

Цельные твердосплавные сверла



укороченное • KCPK15



удлинненное • KCPK15

		диаметр D1			диаметр проволоки	L5	LS	D
		мм	дюйм	значение				
B224A05106HP	B225A05106HP	5,106	.2010	—	7	1,0	36	6
B224A05159HP	B225A05159HP	5,159	.2031	13/64	—	1,0	36	6
—	B225A05200HP	5,200	.2047	—	—	1,0	36	6
—	B225A05300HP	5,300	.2087	—	—	1,0	36	6
—	B225A05400HP	5,400	.2126	—	—	1,0	36	6
B224A05410HP	B225A05410HP	5,410	.2130	—	3	1,0	36	6
B224A05500HP	B225A05500HP	5,500	.2165	—	—	1,0	36	6
B224A05558HP	B225A05558HP	5,558	.2188	7/32	—	1,0	36	6
B224A05600HP	B225A05600HP	5,600	.2205	—	—	1,1	36	6
B224A05616HP	—	5,616	.2211	—	2	1,1	36	6
—	B225A05700HP	5,700	.2244	—	—	1,1	36	6
B224A05791HP	B225A05791HP	5,791	.2280	—	1	1,1	36	6
—	B225A05800HP	5,800	.2283	—	—	1,1	36	6
—	B225A05900HP	5,900	.2323	—	—	1,1	36	6
B224A05944HP	B225A05944HP	5,944	.2340	—	A	1,1	36	6
B224A05954HP	B225A05954HP	5,954	.2344	15/64	—	1,1	36	6
B224A06000HP	B225A06000HP	6,000	.2362	—	—	1,1	36	6
—	B225A06100HP	6,100	.2402	—	—	1,1	36	8
—	B225A06200HP	6,200	.2441	—	—	1,2	36	8
—	B225A06300HP	6,300	.2480	—	—	1,2	36	8
B224A06350HP	B225A06350HP	6,350	.2500	1/4	E	1,2	36	8
—	B225A06400HP	6,400	.2520	—	—	1,2	36	8
B224A06500HP	B225A06500HP	6,500	.2559	—	—	1,2	36	8
B224A06528HP	B225A06528HP	6,528	.2570	—	F	1,2	36	8
—	B225A06600HP	6,600	.2598	—	—	1,2	36	8
B224A06630HP	—	6,630	.2610	—	G	1,2	36	8
B224A06700HP	B225A06700HP	6,700	.2638	—	—	1,3	36	8
B224A06746HP	B225A06746HP	6,746	.2656	17/64	—	1,3	36	8
B224A06800HP	B225A06800HP	6,800	.2677	—	—	1,3	36	8
—	B225A06900HP	6,900	.2717	—	—	1,3	36	8
B224A06909HP	B225A06909HP	6,909	.2720	—	I	1,3	36	8
B224A07000HP	B225A07000HP	7,000	.2756	—	—	1,3	36	8
—	B225A07100HP	7,100	.2795	—	—	1,3	36	8
B224A07145HP	B225A07145HP	7,145	.2813	9/32	—	1,3	36	8
—	B225A07200HP	7,200	.2835	—	—	1,3	36	8
—	B225A07300HP	7,300	.2874	—	—	1,4	36	8
B224A07366HP	B225A07366HP	7,366	.2900	—	L	1,4	36	8
B224A07400HP	B225A07400HP	7,400	.2913	—	—	1,4	36	8
B224A07500HP	B225A07500HP	7,500	.2953	—	—	1,4	36	8
B224A07541HP	B225A07541HP	7,541	.2969	19/64	—	1,4	36	8
—	B225A07600HP	7,600	.2992	—	—	1,4	36	8
—	B225A07700HP	7,700	.3031	—	—	1,4	36	8
—	B225A07800HP	7,800	.3071	—	—	1,5	36	8
—	B225A07900HP	7,900	.3110	—	—	1,5	36	8
B224A07938HP	B225A07938HP	7,938	.3125	5/16	—	1,5	36	8
B224A08000HP	B225A08000HP	8,000	.3150	—	—	1,5	36	8
—	B225A08100HP	8,100	.3189	—	—	1,5	40	10
B224A08200HP	B225A08200HP	8,200	.3228	—	—	1,5	40	10
—	B225A08300HP	8,300	.3268	—	—	1,6	40	10
B224A08334HP	B225A08334HP	8,334	.3281	21/64	—	1,6	40	10
—	B225A08400HP	8,400	.3307	—	—	1,6	40	10
B224A08433HP	B225A08433HP	8,433	.3320	—	Q	1,6	40	10

(продолжение)

