


Цельные твердосплавные сверла

Сверла HP Beyond™ • Сталь • Внутренний подвод СОЖ




(B224/B225_HP • ~3 x D/~5 x D, продолжение)

Цельные твердосплавные сверла



укороченное • KCPK15



удлинное • KCPK15

		диаметр D1			диаметр проволоки	L5	LS	D
		мм	дюйм	значение				
—	B225A12400HP	12,400	.4882	—	—	2,3	45	14
B224A12500HP	B225A12500HP	12,500	.4921	—	—	2,3	45	14
—	B225A12600HP	12,600	.4961	—	—	2,3	45	14
B224A12700HP	B225A12700HP	12,700	.5000	1/2	—	2,4	45	14
B224A12800HP	B225A12800HP	12,800	.5039	—	—	2,4	45	14
—	B225A12900HP	12,900	.5079	—	—	2,4	45	14
B224A13000HP	B225A13000HP	13,000	.5118	—	—	2,4	45	14
B224A13096HP	—	13,096	.5156	33/64	—	2,4	45	14
B224A13100HP	B225A13100HP	13,100	.5157	—	—	2,4	45	14
—	B225A13200HP	13,200	.5197	—	—	2,5	45	14
—	B225A13300HP	13,300	.5236	—	—	2,5	45	14
—	B225A13400HP	13,400	.5276	—	—	2,5	45	14
B224A13495HP	B225A13495HP	13,495	.5313	17/32	—	2,5	45	14
B224A13500HP	B225A13500HP	13,500	.5315	—	—	2,5	45	14
—	B225A13600HP	13,600	.5354	—	—	2,5	45	14
—	B225A13700HP	13,700	.5394	—	—	2,6	45	14
—	B225A13800HP	13,800	.5433	—	—	2,6	45	14
B224A13891HP	B225A13891HP	13,891	.5469	35/64	—	2,6	45	14
—	B225A13900HP	13,900	.5472	—	—	2,6	45	14
B224A14000HP	B225A14000HP	14,000	.5512	—	—	2,6	45	14
—	B225A14100HP	14,100	.5551	—	—	2,6	48	16
—	B225A14200HP	14,200	.5591	—	—	2,6	48	16
B224A14288HP	B225A14288HP	14,288	.5625	9/16	—	2,7	48	16
—	B225A14300HP	14,300	.5630	—	—	2,7	48	16
—	B225A14400HP	14,400	.5669	—	—	2,7	48	16
B224A14500HP	B225A14500HP	14,500	.5709	—	—	2,7	48	16
—	B225A14600HP	14,600	.5748	—	—	2,7	48	16
B224A14684HP	B225A14684HP	14,684	.5781	37/64	—	2,7	48	16
—	B225A14700HP	14,700	.5787	—	—	2,7	48	16
—	B225A14800HP	14,800	.5827	—	—	2,8	48	16
—	B225A14900HP	14,900	.5866	—	—	2,8	48	16
—	B225A15000HP	15,000	.5906	—	—	2,8	48	16
B224A15083HP	B225A15083HP	15,083	.5938	19/32	—	2,8	48	16
—	B225A15100HP	15,100	.5945	—	—	2,8	48	16
—	B225A15200HP	15,200	.5984	—	—	2,8	48	16
—	B225A15300HP	15,300	.6024	—	—	2,8	48	16
—	B225A15400HP	15,400	.6063	—	—	2,9	48	16
B224A15479HP	B225A15479HP	15,479	.6094	39/64	—	2,9	48	16
B224A15500HP	B225A15500HP	15,500	.6102	—	—	2,9	48	16
B224A15600HP	B225A15600HP	15,600	.6142	—	—	2,9	48	16
—	B225A15700HP	15,700	.6181	—	—	2,9	48	16
—	B225A15800HP	15,800	.6220	—	—	2,9	48	16
B224A15875HP	B225A15875HP	15,875	.6250	5/8	—	3,0	48	16
—	B225A15900HP	15,900	.6260	—	—	3,0	48	16
B224A16000HP	B225A16000HP	16,000	.6299	—	—	3,0	48	16
—	B225A16100HP	16,100	.6339	—	—	3,0	48	18
B224A16500HP	B225A16500HP	16,500	.6496	—	—	3,1	48	18
—	B225A16670HP	16,670	.6563	21/32	—	3,1	48	18

(продолжение)