




(B254/B255/B256_YPC • ~3 x D/~5 x D/~8 x D, продолжение)



укороченное • KCK10



удлиненное • KCK10



сверхдлинное • KCK10

			диаметр D1			диаметр проволоки			L5	LS	D
			мм	дюйм	значение						
B254A08400YPC	—	—	8,400	.3307	—	—	—	2,2	40	10	
B254A08433YPC	B255A08433YPC	—	8,433	.3320	—	Q	—	2,2	40	10	
B254A08500YPC	B255A08500YPC	B256A08500YPC	8,500	.3346	—	—	—	2,2	40	10	
B254A08600YPC	B255A08600YPC	B256A08600YPC	8,600	.3386	—	—	—	2,2	40	10	
B254A08700YPC	B255A08700YPC	B256A08700YPC	8,700	.3425	—	—	—	2,3	40	10	
B254A08733YPC	B255A08733YPC	—	8,733	.3438	11/32	—	—	2,3	40	10	
B254A08800YPC	B255A08800YPC	B256A08800YPC	8,800	.3465	—	—	—	2,3	40	10	
B254A08839YPC	B255A08839YPC	—	8,839	.3480	—	S	—	2,3	40	10	
B254A08900YPC	B255A08900YPC	—	8,900	.3504	—	—	—	2,3	40	10	
B254A09000YPC	B255A09000YPC	B256A09000YPC	9,000	.3543	—	—	—	2,3	40	10	
B254A09093YPC	B255A09093YPC	—	9,093	.3580	—	T	—	2,4	40	10	
B254A09100YPC	B255A09100YPC	B256A09100YPC	9,100	.3583	—	—	—	2,4	40	10	
B254A09129YPC	B255A09129YPC	—	9,129	.3594	23/64	—	—	2,4	40	10	
B254A09200YPC	B255A09200YPC	B256A09200YPC	9,200	.3622	—	—	—	2,4	40	10	
—	B255A09300YPC	B256A09300YPC	9,300	.3661	—	—	—	2,4	40	10	
—	—	B256A09347YPC	9,347	.3680	—	U	—	2,4	40	10	
B254A09400YPC	B255A09400YPC	B256A09400YPC	9,400	.3701	—	—	—	2,4	40	10	
B254A09500YPC	B255A09500YPC	B256A09500YPC	9,500	.3740	—	—	—	2,5	40	10	
B254A09525YPC	B255A09525YPC	—	9,525	.3750	3/8	—	—	2,5	40	10	
—	B255A09600YPC	B256A09600YPC	9,600	.3780	—	—	—	2,5	40	10	
—	B255A09700YPC	B256A09700YPC	9,700	.3819	—	—	—	2,5	40	10	
B254A09800YPC	B255A09800YPC	B256A09800YPC	9,800	.3858	—	—	—	2,5	40	10	
B254A09921YPC	B255A09921YPC	—	9,921	.3906	25/64	—	—	2,6	40	10	
B254A10000YPC	B255A10000YPC	B256A10000YPC	10,000	.3937	—	—	—	2,6	40	10	
B254A10200YPC	B255A10200YPC	B256A10200YPC	10,200	.4016	—	—	—	2,6	45	12	
B254A10262YPC	B255A10262YPC	—	10,262	.4040	—	Y	—	2,6	45	12	
B254A10300YPC	B255A10300YPC	B256A10300YPC	10,300	.4055	—	—	—	2,6	45	12	
B254A10320YPC	B255A10320YPC	—	10,320	.4063	13/32	—	—	2,7	45	12	
B254A10400YPC	B255A10400YPC	B256A10400YPC	10,400	.4094	—	—	—	2,7	45	12	
B254A10490YPC	B255A10490YPC	—	10,490	.4130	—	Z	—	2,7	45	12	
B254A10500YPC	B255A10500YPC	B256A10500YPC	10,500	.4134	—	—	—	2,7	45	12	
—	B255A10600YPC	—	10,600	.4173	—	—	—	2,7	45	12	
B254A10700YPC	—	B256A10700YPC	10,700	.4213	—	—	—	2,7	45	12	
B254A10716YPC	B255A10716YPC	—	10,716	.4219	27/64	—	—	2,7	45	12	
B254A10800YPC	B255A10800YPC	B256A10800YPC	10,800	.4252	—	—	—	2,8	45	12	
B254A10900YPC	B255A10900YPC	—	10,900	.4291	—	—	—	2,8	45	12	
B254A11000YPC	B255A11000YPC	B256A11000YPC	11,000	.4331	—	—	—	2,8	45	12	
B254A11100YPC	B255A11100YPC	—	11,100	.4370	—	—	—	2,8	45	12	
B254A11113YPC	B255A11113YPC	—	11,113	.4375	7/16	—	—	2,8	45	12	
B254A11200YPC	B255A11200YPC	B256A11200YPC	11,200	.4409	—	—	—	2,9	45	12	
—	B255A11300YPC	B256A11300YPC	11,300	.4449	—	—	—	2,9	45	12	
B254A11500YPC	B255A11500YPC	B256A11500YPC	11,500	.4528	—	—	—	2,9	45	12	
B254A11509YPC	B255A11509YPC	—	11,509	.4531	29/64	—	—	2,9	45	12	
—	—	B256A11600YPC	11,600	.4567	—	—	—	3,0	45	12	
—	B255A11700YPC	—	11,700	.4606	—	—	—	3,0	45	12	
B254A11800YPC	B255A11800YPC	B256A11800YPC	11,800	.4646	—	—	—	3,0	45	12	
B254A11900YPC	B255A11900YPC	—	11,900	.4685	—	—	—	3,0	45	12	
B254A11908YPC	B255A11908YPC	—	11,908	.4688	15/32	—	—	3,0	45	12	
B254A12000YPC	B255A12000YPC	B256A12000YPC	12,000	.4724	—	—	—	3,1	45	12	
—	B255A12100YPC	—	12,100	.4764	—	—	—	3,1	45	14	
B254A12200YPC	B255A12200YPC	B256A12200YPC	12,200	.4803	—	—	—	3,1	45	14	
B254A12251YPC	B255A12251YPC	—	12,251	.4823	—	—	—	3,1	45	14	

(продолжение)

Цельные твердосплавные сверла