

(B269_HP • ~12 х D, продолжение)



КСРК15	диаметр D1			диаметр проволоки	L	L3	L4 max	L5	LS	D
	мм	дюйм	значение							
B269A08500HP	8,500	.3346	—	—	185	137	117	1,6	40	10
B269A08700HP	8,700	.3425	—	—	185	138	118	1,6	40	10
B269A08733HP	8,733	.3438	11/32	—	185	138	117	1,6	40	10
B269A09000HP	9,000	.3543	—	—	185	139	118	1,7	40	10
B269A09100HP	9,100	.3583	—	—	185	139	118	1,7	40	10
B269A09129HP	9,129	.3594	23/64	—	185	139	118	1,7	40	10
B269A09500HP	9,500	.3740	—	—	185	140	119	1,8	40	10
B269A09525HP	9,525	.3750	3/8	—	185	140	119	1,8	40	10
B269A09921HP	9,921	.3906	25/64	—	185	142	120	1,9	40	10
B269A10000HP	10,000	.3937	—	—	185	142	120	1,9	40	10
B269A10200HP	10,200	.4016	—	—	218	164	140	1,9	45	12
B269A10300HP	10,300	.4055	—	—	218	165	141	1,9	45	12
B269A10320HP	10,320	.4063	13/32	—	218	165	141	1,9	45	12
B269A10500HP	10,500	.4134	—	—	218	165	141	2,0	45	12
B269A10716HP	10,716	.4219	27/64	—	218	166	142	2,0	45	12
B269A10800HP	10,800	.4252	—	—	218	166	141	2,0	45	12
B269A11000HP	11,000	.4331	—	—	218	167	142	2,1	45	12
B269A11113HP	11,113	.4375	7/16	—	218	167	142	2,1	45	12
B269A11500HP	11,500	.4528	—	—	218	168	143	2,1	45	12
B269A11800HP	11,800	.4646	—	—	218	169	143	2,2	45	12
B269A12000HP	12,000	.4724	—	—	218	170	144	2,2	45	12
B269A12100HP	12,100	.4764	—	—	246	192	164	2,3	45	14
B269A12304HP	12,304	.4844	31/64	—	246	193	165	2,3	45	14
B269A12500HP	12,500	.4921	—	—	246	193	165	2,3	45	14
B269A12700HP	12,700	.5000	1/2	—	246	194	166	2,4	45	14
B269A13000HP	13,000	.5118	—	—	246	195	166	2,4	45	14
B269A13100HP	13,100	.5157	—	—	246	195	166	2,4	45	14
B269A13500HP	13,500	.5315	—	—	246	196	167	2,5	45	14
B269A14000HP	14,000	.5512	—	—	246	198	168	2,6	45	14
B269A14100HP	14,100	.5551	—	—	277	220	188	2,6	48	16
B269A14288HP	14,288	.5625	9/16	—	277	220	188	2,7	48	16
B269A14500HP	14,500	.5709	—	—	277	221	189	2,7	48	16
B269A14684HP	14,684	.5781	37/64	—	277	222	190	2,7	48	16
B269A15000HP	15,000	.5906	—	—	277	223	190	2,8	48	16
B269A15500HP	15,500	.6102	—	—	277	224	191	2,9	48	16
B269A15875HP	15,875	.6250	5/8	—	277	225	192	3,0	48	16
B269A16000HP	16,000	.6299	—	—	277	226	192	3,0	48	16
B269A16500HP	16,500	.6496	—	—	305	249	213	3,1	48	18
B269A17000HP	17,000	.6693	—	—	305	250	214	3,2	48	18
B269A17463HP	17,463	.6875	11/16	—	305	252	215	3,2	48	18
B269A17500HP	17,500	.6890	—	—	305	252	215	3,3	48	18
B269A18000HP	18,000	.7087	—	—	305	253	216	3,3	48	18
B269A18500HP	18,500	.7283	—	—	334	277	237	3,4	50	20
B269A19000HP	19,000	.7480	—	—	334	278	238	3,5	50	20
B269A19050HP	19,050	.7500	3/4	—	334	279	239	3,5	50	20
B269A19500HP	19,500	.7677	—	—	334	280	239	3,6	50	20
B269A20000HP	20,000	.7874	—	—	334	281	240	3,7	50	20

Точность изготовления • Метрическая система

диапазон номинальных размеров	D1 допуск m7	D допуск h6
>3-6	0,004/0,016	0,000/-0,008
>6-10	0,006/0,021	0,000/-0,009
>10-18	0,007/0,025	0,000/-0,011
>18-25,4	0,008/0,029	0,000/-0,013