



(B273Z_HPG/HPS • 25 x D, продолжение)



KC7425



KN25

		диаметр D1									
		мм	дюйм	значение	диаметр проволоки	L	L3	L4 max	L5	LS	D
B273Z10200HPG	B273Z10200HPS	10,200	.4016	—	—	348	288	265	1,9	46	11
B273Z10500HPG	B273Z10500HPS	10,500	.4134	—	—	348	292	269	1,9	46	11
B273Z10720HPG	B273Z10720HPS	10,720	.4220	—	—	348	295	272	2,0	46	11
B273Z11000HPG	B273Z11000HPS	11,000	.4331	—	—	348	299	275	2,0	46	11
B273Z11500HPG	B273Z11500HPS	11,500	.4528	—	—	377	319	294	2,1	48	12
B273Z12000HPG	B273Z12000HPS	12,000	.4724	—	—	377	326	300	2,2	48	12
B273Z12500HPG	B273Z12500HPS	12,500	.4921	—	—	406	346	319	2,3	50	13
B273Z12700HPG	B273Z12700HPS	12,700	.5000	1/2	—	406	349	322	2,3	50	13
B273Z13000HPG	B273Z13000HPS	13,000	.5118	—	—	406	353	325	2,4	50	13
B273Z13100HPG	B273Z13100HPS	13,100	.5157	—	—	435	368	339	2,4	52	14
B273Z13500HPG	B273Z13500HPS	13,500	.5315	—	—	435	373	344	2,5	52	14
B273Z14000HPG	B273Z14000HPS	14,000	.5512	—	—	435	380	350	2,6	52	14
B273Z14290HPG	B273Z14290HPS	14,290	.5626	—	—	464	397	366	2,6	54	15
B273Z14500HPG	B273Z14500HPS	14,500	.5709	—	—	464	400	369	2,7	54	15
B273Z15000HPG	B273Z15000HPS	15,000	.5906	—	—	464	407	375	2,8	54	15

Цельные твердосплавные сверла