



(B274Z\_HPG/HPS • 30 x D, продолжение)



KC7425



KN25

		диаметр D1									
		мм	дюйм	значение	диаметр проволоки	L	L3	L4 max	L5	LS	D
B274Z08000HPG	B274Z08000HPS	8,000	.3150	—	—	301	258	240	1,5	40	8
B274Z08334HPG	—	8,334	.3281	21/64	—	335	278	259	1,5	42	9
B274Z08500HPG	B274Z08500HPS	8,500	.3346	—	—	335	281	262	1,6	42	9
—	B274Z08733HPS	8,733	.3438	11/32	—	335	285	265	1,6	42	9
B274Z09000HPG	B274Z09000HPS	9,000	.3543	—	—	335	290	270	1,7	42	9
B274Z09100HPG	—	9,100	.3583	—	—	369	306	285	1,7	44	10
B274Z09525HPG	B274Z09525HPS	9,525	.3750	3/8	—	369	313	292	1,8	44	10
B274Z10000HPG	B274Z10000HPS	10,000	.3937	—	—	369	322	300	1,8	44	10
B274Z10200HPG	B274Z10200HPS	10,200	.4016	—	—	403	339	316	1,9	46	11
B274Z10500HPG	B274Z10500HPS	10,500	.4134	—	—	403	345	322	1,9	46	11
B274Z10720HPG	B274Z10720HPS	10,720	.4220	—	—	403	349	326	2,0	46	11
B274Z11000HPG	B274Z11000HPS	11,000	.4331	—	—	403	354	330	2,0	46	11
B274Z11500HPG	—	11,500	.4528	—	—	437	377	363	2,1	48	12
—	B274Z11500HPS	11,500	.4528	—	—	437	377	352	2,1	48	12
B274Z12000HPG	B274Z12000HPS	12,000	.4724	—	—	437	386	360	2,2	48	12
B274Z12500HPG	B274Z12500HPS	12,500	.4921	—	—	471	409	382	2,3	50	13
B274Z12700HPG	B274Z12700HPS	12,700	.5000	1/2	—	471	412	385	2,3	50	13
B274Z13000HPG	B274Z13000HPS	13,000	.5118	—	—	471	418	390	2,4	50	13

Цельные твердосплавные сверла

Точность изготовления • Метрическая система

диапазон номинальных размеров	D1 HPG допуск h7	D1HPS допуск h8	D допуск h6
1–3	0,000/-0,010	0,000/-0,014	0,000/-0,006
>3–6	0,000/-0,012	0,000/-0,018	0,000/-0,008
>6–10	0,000/-0,015	0,000/-0,022	0,000/-0,009
>10–18	0,000/-0,018	0,000/-0,027	0,000/-0,011