


Сведения о L, L3 и L4 тах приведены в таблице на вкладке «Цельные твердосплавные сверла».




Цельные твердосплавные сверла

■ B291/B292_YPL • ~3 x D/~5 x D



укороченное • KC7315



удлиненное • KC7315

- лучший выбор
- альтернативный выбор

		диаметр D1							
		мм	дюйм	значение	диаметр проволоки	L5	LS	D	
B291A03000YPL	B292A03000YPL	3,000	.1181	—	—	0,6	36	6	
B291A03100YPL	B292A03100YPL	3,100	.1220	—	—	0,6	36	6	
B291A03175YPL	B292A03175YPL	3,175	.1250	1/8	—	0,6	36	6	
B291A03200YPL	B292A03200YPL	3,200	.1260	—	—	0,6	36	6	
B291A03300YPL	B292A03300YPL	3,300	.1299	—	—	0,7	36	6	
B291A03400YPL	B292A03400YPL	3,400	.1339	—	—	0,7	36	6	
B291A03454YPL	B292A03454YPL	3,454	.1360	—	29	0,7	36	6	
B291A03500YPL	B292A03500YPL	3,500	.1378	—	—	0,7	36	6	
B291A03600YPL	B292A03600YPL	3,600	.1417	—	—	0,7	36	6	
B291A03700YPL	B292A03700YPL	3,700	.1457	—	—	0,7	36	6	
B291A03800YPL	B292A03800YPL	3,800	.1496	—	—	0,8	36	6	
B291A03900YPL	B292A03900YPL	3,900	.1535	—	—	0,8	36	6	
B291A03970YPL	B292A03970YPL	3,970	.1563	5/32	—	0,8	36	6	
B291A04000YPL	B292A04000YPL	4,000	.1575	—	—	0,8	36	6	
B291A04100YPL	B292A04100YPL	4,100	.1614	—	—	0,8	36	6	
—	B292A04200YPL	4,200	.1654	—	—	0,8	36	6	
B291A04300YPL	B292A04300YPL	4,300	.1693	—	—	0,8	36	6	
B291A04400YPL	—	4,400	.1732	—	—	0,9	36	6	
B291A04500YPL	B292A04500YPL	4,500	.1772	—	—	0,9	36	6	
—	B292A04700YPL	4,700	.1850	—	13	0,9	36	6	
B291A04763YPL	B292A04763YPL	4,763	.1875	3/16	—	0,9	36	6	
B291A04800YPL	B292A04800YPL	4,800	.1890	—	12	0,9	36	6	
B291A04851YPL	B292A04851YPL	4,851	.1910	—	11	0,9	36	6	
B291A04900YPL	—	4,900	.1929	—	—	0,9	36	6	
B291A04915YPL	B292A04915YPL	4,915	.1935	—	10	1,0	36	6	
B291A05000YPL	B292A05000YPL	5,000	.1969	—	—	1,0	36	6	
B291A05100YPL	B292A05100YPL	5,100	.2008	—	—	1,0	36	6	
B291A05200YPL	B292A05200YPL	5,200	.2047	—	—	1,0	36	6	
B291A05410YPL	B292A05410YPL	5,410	.2130	—	3	1,1	36	6	
B291A05500YPL	B292A05500YPL	5,500	.2165	—	—	1,1	36	6	
—	B292A05558YPL	5,558	.2188	7/32	—	1,1	36	6	
B291A05600YPL	B292A05600YPL	5,600	.2205	—	—	1,1	36	6	
—	B292A05800YPL	5,800	.2283	—	—	1,1	36	6	
B291A05900YPL	—	5,900	.2323	—	—	1,1	36	6	
B291A06000YPL	B292A06000YPL	6,000	.2362	—	—	1,2	36	6	
B291A06200YPL	B292A06200YPL	6,200	.2441	—	—	1,2	36	8	
B291A06350YPL	B292A06350YPL	6,350	.2500	1/4	E	1,2	36	8	
B291A06500YPL	B292A06500YPL	6,500	.2559	—	—	1,3	36	8	
—	B292A06528YPL	6,528	.2570	—	F	1,3	36	8	
—	B292A06600YPL	6,600	.2598	—	—	1,3	36	8	

(продолжение)