


Цельные твердосплавные сверла

Сверла с плоским торцом 180° • Внутренний подвод СОЖ




(B707_FBG/FBS/FBL • ~3 x D, продолжение)


Цельные твердосплавные сверла



B707A-FBG • KC7315



B707A-FBS • KN15



B707A-FBL • KC7315

			диаметр D1				L4 max	L3	L	LS	D
			мм	дюйм	значение	диаметр проволоки					
B707A10600FBG	—	—	10,600	.4173	—	—	40	55	102	45	12
B707A11000FBG	B707A11000FBS	B707A11000FBL	11,000	.4331	—	—	40	55	102	45	12
B707A11111FBG	B707A11111FBS	B707A11111FBL	11,111	.4374	—	—	40	55	102	45	12
B707A11509FBG	B707A11509FBS	B707A11509FBL	11,509	.4531	29/64	—	40	55	102	45	12
B707A11570FBG	B707A11570FBS	B707A11570FBL	11,570	.4555	—	—	40	55	102	45	12
B707A11700FBG	B707A11700FBS	B707A11700FBL	11,700	.4606	—	—	40	55	102	45	12
B707A11800FBG	B707A11800FBS	B707A11800FBL	11,800	.4646	—	—	40	55	102	45	12
B707A11908FBG	—	—	11,908	.4688	15/32	—	40	55	102	45	12
B707A12000FBG	B707A12000FBS	B707A12000FBL	12,000	.4724	—	—	40	55	102	45	12
B707A12100FBG	B707A12100FBS	B707A12100FBL	12,100	.4764	—	—	43	60	107	45	14
B707A12500FBG	B707A12500FBS	B707A12500FBL	12,500	.4921	—	—	43	60	107	45	14
B707A12700FBG	B707A12700FBS	B707A12700FBL	12,700	.5000	1/2	—	43	60	107	45	14
B707A12800FBG	B707A12800FBS	B707A12800FBL	12,800	.5039	—	—	43	60	107	45	14
B707A13000FBG	B707A13000FBS	B707A13000FBL	13,000	.5118	—	—	43	60	107	45	14
B707A13500FBG	B707A13500FBS	B707A13500FBL	13,500	.5315	—	—	43	60	107	45	14
B707A14000FBG	B707A14000FBS	B707A14000FBL	14,000	.5512	—	—	43	60	107	45	14
B707A14288FBG	B707A14288FBS	B707A14288FBL	14,288	.5625	9/16	—	45	65	115	48	16
B707A14500FBG	B707A14500FBS	B707A14500FBL	14,500	.5709	—	—	45	65	115	48	16
B707A15000FBG	B707A15000FBS	B707A15000FBL	15,000	.5906	—	—	45	65	115	48	16
B707A15250FBG	B707A15250FBS	B707A15250FBL	15,250	.6004	—	—	45	65	115	48	16
B707A15500FBG	B707A15500FBS	B707A15500FBL	15,500	.6102	—	—	45	65	115	48	16
B707A15875FBG	B707A15875FBS	B707A15875FBL	15,875	.6250	5/8	—	45	65	115	48	16
B707A16000FBG	B707A16000FBS	B707A16000FBL	16,000	.6299	—	—	45	65	115	48	16
B707A16500FBG	B707A16500FBS	B707A16500FBL	16,500	.6496	—	—	51	73	123	48	18
B707A17000FBG	B707A17000FBS	B707A17000FBL	17,000	.6693	—	—	51	73	123	48	18
B707A17463FBG	—	—	17,463	.6875	11/16	—	51	73	123	48	18
B707A17500FBG	B707A17500FBS	B707A17500FBL	17,500	.6890	—	—	51	73	123	48	18
B707A18000FBG	B707A18000FBS	B707A18000FBL	18,000	.7087	—	—	51	73	123	48	18
B707A18500FBG	—	—	18,500	.7283	—	—	55	79	131	50	20
B707A19000FBG	B707A19000FBS	B707A19000FBL	19,000	.7480	—	—	55	79	131	50	20
B707A19050FBG	B707A19050FBS	B707A19050FBL	19,050	.7500	3/4	—	55	79	131	50	20
B707A20000FBG	B707A20000FBS	B707A20000FBL	20,000	.7874	—	—	55	79	131	50	20
B707A21000FBG	B707A21000FBS	B707A21000FBL	21,000	.8268	—	—	60	86	141	50	20

Точность изготовления • Метрическая система

диапазон номинальных размеров	D1 допуск m7	D допуск h6
>3-6	0,004/0,016	0,000/-0,008
>6-10	0,006/0,021	0,000/-0,009
>10-18	0,007/0,025	0,000/-0,011
>18-25,4	0,008/0,029	0,000/-0,013

