


■ B966 • ~3 x D



- лучший выбор
- альтернативный выбор

укороченное • KC7315	диаметр D1				L	L4 max	L5	LS	D
	мм	дюйм	значение	диаметр проволоки					
B966A03000	3,000	.1181	—	—	62	14	0,5	36	6
B966A03100	3,100	.1220	—	—	62	14	0,5	36	6
B966A03200	3,200	.1260	—	—	62	14	0,5	36	6
B966A03300	3,300	.1299	—	—	62	14	0,5	36	6
B966A03400	3,400	.1339	—	—	62	14	0,6	36	6
B966A03500	3,500	.1378	—	—	62	14	0,6	36	6
B966A03600	3,600	.1417	—	—	62	14	0,6	36	6
B966A03700	3,700	.1457	—	—	62	14	0,6	36	6
B966A03800	3,800	.1496	—	—	66	17	0,6	36	6
B966A03900	3,900	.1535	—	—	66	17	0,6	36	6
B966A04000	4,000	.1575	—	—	66	17	0,7	36	6
B966A04100	4,100	.1614	—	—	66	17	0,7	36	6
B966A04200	4,200	.1654	—	—	66	17	0,7	36	6
B966A04300	4,300	.1693	—	—	66	17	0,7	36	6
B966A04400	4,400	.1732	—	—	66	17	0,7	36	6
B966A04500	4,500	.1772	—	—	66	17	0,7	36	6
B966A04600	4,600	.1811	—	—	66	17	0,8	36	6
B966A04700	4,700	.1850	—	13	66	17	0,8	36	6
B966A04800	4,800	.1890	—	12	66	20	0,8	36	6
B966A04900	4,900	.1929	—	—	66	20	0,8	36	6
B966A05000	5,000	.1969	—	—	66	20	0,8	36	6
B966A05100	5,100	.2008	—	—	66	20	0,8	36	6
B966A05200	5,200	.2047	—	—	66	20	0,9	36	6
B966A05300	5,300	.2087	—	—	66	20	0,9	36	6
B966A05400	5,400	.2126	—	—	66	20	0,9	36	6
B966A05500	5,500	.2165	—	—	66	20	0,9	36	6
B966A05600	5,600	.2205	—	—	66	20	0,9	36	6
B966A05700	5,700	.2244	—	—	66	20	1,0	36	6
B966A05800	5,800	.2283	—	—	66	20	1,0	36	6
B966A05900	5,900	.2323	—	—	66	20	1,0	36	6
B966A06000	6,000	.2362	—	—	66	20	1,0	36	6
B966A06100	6,100	.2402	—	—	79	24	1,0	36	8
B966A06200	6,200	.2441	—	—	79	24	1,0	36	8
B966A06300	6,300	.2480	—	—	79	24	1,1	36	8
B966A06400	6,400	.2520	—	—	79	24	1,1	36	8
B966A06500	6,500	.2559	—	—	79	24	1,1	36	8

(продолжение)