

■ VNMP-K



Номер по каталогу ISO	Номер по каталогу ANSI	D		L10		S		Re		D1	
		мм	дюйм	мм	дюйм	мм	дюйм	мм	дюйм	мм	дюйм
VNMP160404K	VNMP331K	9,53	3/8	16,61	.654	4,76	3/16	0,4	1/64	3,81	.150
VNMP160408K	VNMP332K	9,53	3/8	16,61	.654	4,76	3/16	0,8	1/32	3,81	.150

■ VNMS



VNMS160404	VNMS331	9,53	3/8	16,61	.654	4,76	3/16	0,4	1/64	3,81	.150
VNMS160408	VNMS332	9,53	3/8	16,61	.654	4,76	3/16	0,8	1/32	3,81	.150

■ WNGA-F



(ST)

WNGA080404FST	WNGA431FST	12,70	1/2	8,69	.342	4,76	3/16	0,4	1/64	5,16	.203
WNGA080408FST	WNGA432FST	12,70	1/2	8,69	.342	4,76	3/16	0,8	1/32	5,16	.203

■ WNGA-FW



(MT)

WNGA080408S01020FWMT	WNGA432S0420FWMT	12,70	1/2	8,69	.342	4,76	3/16	0,8	1/32	5,16	.203
WNGA080412S01020FWMT	WNGA433S0420FWMT	12,70	1/2	8,69	.342	4,76	3/16	1,2	3/64	5,16	.203

■ WNGA



(MT)


WNGA080404S01020MT	WNGA431S0420MT	12,70	1/2	8,69	.342	4,76	3/16	0,4	1/64	5,16	.203
WNGA080404S01025MT	WNGA431S0425MT	12,70	1/2	8,69	.342	4,76	3/16	0,4	1/64	5,16	.203
WNGA080408S01020MT	WNGA432S0420MT	12,70	1/2	8,69	.342	4,76	3/16	0,8	1/32	5,16	.203
WNGA080408S01025MT	WNGA432S0425MT	12,70	1/2	8,69	.342	4,76	3/16	0,8	1/32	5,16	.203
WNGA080412S01020MT	WNGA433S0420MT	12,70	1/2	8,69	.342	4,76	3/16	1,2	3/64	5,16	.203

■ WNMA-MW



WNMA080408S02020MW	WNMA432S0820MW	12,70	1/2	8,69	.342	4,76	3/16	0,8	1/32	5,16	.203
--------------------	----------------	-------	-----	------	------	------	------	-----	------	------	------

■ WNMA



WNMA080408S02020	WNMA432S0820	12,70	1/2	8,69	.342	4,76	3/16	0,8	1/32	5,16	.203
WNMA080412E	WNMA433E	12,70	1/2	8,69	.342	4,76	3/16	1,2	3/64	5,16	.203

■ WNGA-FW



WNGA080408EFW	WNGA432FW	12,70	1/2	8,69	.342	4,76	3/16	0,8	1/32	5,16	.203
WNGA080408T01020FW	WNGA432T0420FW	12,70	1/2	8,69	.342	4,76	3/16	0,8	1/32	5,16	.203
WNGA080412EFW	WNGA433FW	12,70	1/2	8,69	.342	4,76	3/16	1,2	3/64	5,16	.203
WNGA080412T01020FW	WNGA433T0420FW	12,70	1/2	8,69	.342	4,76	3/16	1,2	3/64	5,16	.203

Пример заказа:

Номер по каталогу ISO: WNGA080408EFW

Сплав: KY4400