



● лучший выбор

○ альтернативный выбор

| H | S | N | K | M | P |
|---|---|---|---|---|---|
|   | ● | ● | ● | ● | ● |
|   | ● | ● | ● | ● | ● |
|   | ● | ● | ● | ● | ● |
|   | ● | ● | ● | ● | ● |
|   | ● | ● | ● | ● | ● |




## ■ NAS




Укороченная трапецидальная резьба Асте

| Размер пластины | Номер по каталогу | TPI | TPF | RC |   | CF    |       | E    |      | K68 | KC5010 | KC5025 | KC5410 |
|-----------------|-------------------|-----|-----|----|---|-------|-------|------|------|-----|--------|--------|--------|
|                 | <b>Правая</b>     |     |     |    |   |       |       |      |      |     |        |        |        |
| 3               | NAS3R16           | 16  | —   | —  | — | 0,605 | .0238 | 3,79 | .149 |     | ●      |        |        |
| 3               | NAS3R14           | 14  | —   | —  | — | 0,701 | .0276 | 3,79 | .149 |     | ●      |        |        |
| 3               | NAS3R12           | 12  | —   | —  | — | 0,828 | .0326 | 3,79 | .149 |     | ●      |        |        |
| 3               | NAS3R10           | 10  | —   | —  | — | 0,940 | .0370 | 3,79 | .149 |     | ●      |        |        |
| 3               | NAS3R8            | 8   | —   | —  | — | 1,209 | .0476 | 3,79 | .149 |     | ●      |        |        |
| 3               | NAS3R6            | 6   | —   | —  | — | 1,656 | .0652 | 3,79 | .149 |     | ●      |        |        |
| 3               | NAS3R5            | 5   | —   | —  | — | 2,014 | .0793 | 3,79 | .149 |     | ●      |        |        |
|                 | <b>Левая</b>      |     |     |    |   |       |       |      |      |     |        |        |        |
| 3               | NAS3L16           | 16  | —   | —  | — | 0,605 | .0238 | 3,79 | .149 |     | ●      |        |        |
| 3               | NAS3L12           | 12  | —   | —  | — | 0,828 | .0326 | 3,79 | .149 |     | ●      |        |        |
| 3               | NAS3L10           | 10  | —   | —  | — | 0,940 | .0370 | 3,79 | .149 |     | ●      |        |        |
| 3               | NAS3L8            | 8   | —   | —  | — | 1,209 | .0476 | 3,79 | .149 |     | ●      |        |        |
| 3               | NAS3L6            | 6   | —   | —  | — | 1,656 | .0652 | 3,79 | .149 |     | ●      |        |        |
| 3               | NAS3L5            | 5   | —   | —  | — | 2,014 | .0793 | 3,79 | .149 |     | ●      |        |        |




## ■ NTB-A




Американская пилообразная Buttress - на сжатие

| Размер пластины | Номер по каталогу | TPI   | TPF | RC    |       | CF |   | E    |      | K68 | KC5010 | KC5025 | KC5410 |
|-----------------|-------------------|-------|-----|-------|-------|----|---|------|------|-----|--------|--------|--------|
|                 | <b>Правая</b>     |       |     |       |       |    |   |      |      |     |        |        |        |
| 2               | NTB2RA            | 16-20 | —   | 0,076 | .0030 | —  | — | 3,20 | .126 | ●   | ●      |        |        |
| 3               | NTB3RA            | 8-16  | —   | 0,165 | .0065 | —  | — | 4,17 | .164 | ●   | ●      |        |        |
| 4               | NTB4RA            | 4-6   | —   | 0,254 | .0100 | —  | — | 5,23 | .206 | ●   | ●      |        |        |
|                 | <b>Левая</b>      |       |     |       |       |    |   |      |      |     |        |        |        |
| 2               | NTB2LA            | 16-20 | —   | 0,076 | .0030 | —  | — | 3,20 | .126 |     |        | ●      |        |
| 3               | NTB3LA            | 8-16  | —   | 0,165 | .0065 | —  | — | 4,17 | .164 | ●   | ●      | ●      |        |
| 4               | NTB4LA            | 4-6   | —   | 0,254 | .0100 | —  | — | 5,23 | .206 | ●   | ●      | ●      |        |



## ■ NTB-B



Американская пилообразная Buttress - на сжатие

| Размер пластины | Номер по каталогу | TPI   | TPF | RC    |       | CF |   | E    |      | K68 | KC5010 | KC5025 | KC5410 |
|-----------------|-------------------|-------|-----|-------|-------|----|---|------|------|-----|--------|--------|--------|
|                 | <b>Правая</b>     |       |     |       |       |    |   |      |      |     |        |        |        |
| 2               | NTB2RB            | 16-20 | —   | 0,076 | .0030 | —  | — | 0,25 | .010 |     | ●      | ●      |        |
| 3               | NTB3RB            | 8-16  | —   | 0,165 | .0065 | —  | — | 0,31 | .012 | ●   | ●      | ●      |        |
| 4               | NTB4RB            | 4-6   | —   | 0,254 | .0100 | —  | — | 0,41 | .016 |     | ●      | ●      |        |
|                 | <b>Левая</b>      |       |     |       |       |    |   |      |      |     |        |        |        |
| 2               | NTB2LB            | 16-20 | —   | 0,076 | .0030 | —  | — | 0,25 | .010 |     | ●      |        |        |
| 3               | NTB3LB            | 8-16  | —   | 0,165 | .0065 | —  | — | 0,31 | .012 | ●   | ●      | ●      |        |
| 4               | NTB4LB            | 4-6   | —   | 0,254 | .0100 | —  | — | 0,41 | .016 |     | ●      | ●      |        |

Пример заказа:

Номер по каталогу: NTB2RB

Марка сплава: KC5010

ПРИМЕЧАНИЕ. Рекомендации по выбору пластин для обработки американской резьбы см. стр. E78-E79.