


● лучший выбор
○ альтернативный выбор

H				
S				
N				
K				
M				
P				




■ LT-ER/L-60



Неполный
профиль 60°
(наружная)

Размер пластины	Номер по каталогу	Рабочая поверхность в мм	TPI	TPF	RC		EX		E		KC5010	KC5025	KU25T
	Правая												
16	LT16ERA60	0,50-1,5	48-16	—	0,05	.002	0,8	.031	0,9	.035	●	●	
16	LT16ERAG60	0,50-3,0	48-8	—	0,08	.003	1,2	.047	1,7	.067	●	●	
16	LT16ERG60	1,75-3,0	14-8	—	0,28	.011	1,2	.047	1,7	.067	●	●	
22	LT22ERN60	3,5-5,0	7-5	—	0,53	.021	1,7	.067	2,5	.098		●	
	Левая												
16	LT16ELA60	0,50-1,5	48-16	—	0,05	.002	0,8	.031	0,9	.035		●	
16	LT16ELAG60	0,50-3,0	48-8	—	0,08	.003	1,2	.047	1,7	.067		●	
16	LT16ELG60	1,75-3,0	14-8	—	0,28	.011	1,2	.047	1,7	.067		●	
22	LT22ELN60	3,5-5,0	7-5	—	0,53	.021	1,7	.067	2,5	.098		●	



■ LT-NR/L-60



Неполный
профиль 60°
(внутренняя)

Размер пластины	Номер по каталогу	Рабочая поверхность в мм	TPI	TPF	RC		EX		E		KC5010	KC5025	KU25T
	Правая												
11	LT11NRA60	0,50-1,5	48-16	—	0,05	.002	0,8	.031	0,9	.035	●	●	
16	LT16NRA60	0,50-1,5	48-16	—	0,05	.002	0,8	.031	0,9	.035	●	●	
16	LT16NRAG60	0,50-3,0	48-8	—	0,05	.002	1,2	.047	1,7	.067	●	●	
16	LT16NRG60	1,75-3,0	14-8	—	0,15	.006	1,2	.047	1,7	.067	●	●	
22	LT22NRN60	3,5-5,0	7-5	—	0,31	.012	1,7	.067	2,5	.098		●	
	Левая												
11	LT11NLA60	0,50-1,5	48-16	—	0,05	.002	0,8	.031	0,9	.035		●	
16	LT16NLA60	0,50-1,5	48-16	—	0,05	.002	0,8	.031	0,9	.035		●	
16	LT16NLAG60	0,50-3,0	48-8	—	0,05	.002	1,2	.047	1,7	.067		●	
16	LT16NLG60	1,75-3,0	14-8	—	0,15	.006	1,2	.047	1,7	.067		●	
22	LT22NLN60	3,5-5,0	7-5	—	0,31	.012	1,7	.067	2,5	.098		●	

Пример заказа:

Номер по каталогу: LT16ERAG60CB

Марка сплава: KC5010