




■ GS-N

	Номер по каталогу ISO	Номер по каталогу ANSI	W		R max		α	KC720	KC722	KC935
			мм	дюйм	мм	дюйм				
	GS24N	GS094N	2,39	.094	0,08	.003	—	●	●	●
	GS32N	GS125N	3,20	.126	0,08	.003	—	●	●	●
	GS40N	GS160N	4,06	.160	0,08	.003	—	●	●	●
	GS48N	GS188N	4,78	.188	0,08	.003	—	●	●	●
	GS64N	GS250N	6,35	.250	0,08	.003	—	●	●	●

■ GS-R

	GS24R	GS094R	2,39	.094	0,08	.003	4	●	●	●
	GS24R12	GS094R12	2,36	.093	0,05	.002	12	●	●	●
	GS24R18	GS094R18	2,34	.092	0,05	.002	18	●	●	●
	GS32R	GS125R	3,18	.125	0,08	.003	4	●	●	●
	GS32R12	GS125R12	3,18	.125	0,05	.002	12	●	●	●
	GS32R18	GS125R18	3,15	.124	0,05	.002	18	●	●	●
	GS40R	GS160R	4,04	.159	0,08	.003	4	●	●	●
	GS48R	GS188R	4,75	.187	0,08	.003	4	●	●	●

■ GS-L

	GS24L	GS094L	2,39	.094	0,08	.003	4	●	●	●
	GS32L	GS125L	3,18	.125	0,08	.003	4	●	●	●
	GS32L12	GS125L12	3,18	.125	0,05	.002	12	●	●	●
	GS48L	GS188L	4,75	.187	0,08	.003	4	●	●	●

Пример заказа:

Номер по каталогу ISO: GS24L

Марка детали: KC720

ПРИМЕЧАНИЕ: Посмотреть полный список деталей с глубокими канавками KENDEX можно на сайте www.kennametal.su