



KENLOC™

■ Зажимной штифт

Номер по каталогу	размер резьбы	верхний ключ шестигранник (дюймы)	нижний ключ шестигранник (дюймы)	рекомендуемый крутящий момент		
				Нм	дюйм-фунт	фут-фунт
KL23	#8-32	—	1/16	1,5	13	1.0
KL33	#10-32	5/64	5/64	1,7	15	1.2
KL33L	#10-32	5/64	5/64	1,7	15	1.2
KL34	#10-32	5/64	5/64	1,7	15	1.2
KL34L	#10-32	5/64	5/64	1,7	15	1.2
KL44	1/4-28	3/32	3/32	3,3	30	2.5
KL46	1/4-28	3/32	3/32	3,3	30	2.5
KL46L	1/4-28	3/32	3/32	3,3	30	2.5
KL57	5/16-24	1/8	1/8	5,5	50	4.0
KL58	5/16-24	1/8	1/8	5,5	50	4.0
KL58L	5/16-24	1/8	1/8	5,5	50	4.0
KL68	3/8-24	9/64	9/64	8,0	70	5.6
KL68L	3/8-24	9/64	9/64	8,0	70	5.6
KL810	7/16-20	5/32	5/32	9,0	80	6.4
KLC33	M5 x 0,8	5/64	5/64	1,7	15	1.2
KLC33L	M5 x 0,8	5/64	5/64	1,7	15	1.2
KLC34L	M5 x 0,8	5/64	5/64	1,7	15	1.2
KLC43	M5 x 0,8	5/64	5/64	1,7	15	1.2
KLC44	M6,3 x 1	3/32	3/32	3,3	30	2.5
KLC46	M6,3 x 1	3/32	3/32	3,3	30	2.5
KLC46L	M6,3 x 1	3/32	3/32	3,3	30	2.5
KLC46S	M6,3 x 1	3/32	3/32	3,3	30	2.5
KLC54	M6,3 x 1	3/32	3/32	3,3	30	2.5
KLC56	M8 x 1	1/8	1/8	5,5	50	4.0
KLC58	M8 x 1	1/8	1/8	5,5	50	4.0
KLC68	M10 x 1	9/64	9/64	8,0	70	5.6
KLC810	M12 x 1,25	5/32	5/32	9,0	80	6.4

■ Зажимной винт

Номер по каталогу	размер резьбы	верхний ключ шестигранник (дюймы)	нижний ключ шестигранник (дюймы)	рекомендуемый крутящий момент		
				Нм	дюйм-фунт	фут-фунт
STC2	5/16-24	5/32	5/32	10,8	96	8
STC3	1/2-20	1/4	1/4	40,3	357	30
STC4	5/16-24	5/32	3/32	10,8	96	8
STC5	10-32	3/32	3/32	2,3	21	1.6
STC8	5/16-24	5/32	5/32	10,8	96	8
STC9	10-32	3/32	3/32	2,3	21	1.6
STC11	1/4-28	1/8	1/8	5,4	48	4
STC12	1/4-28	1/8	1/8	5,4	48	4
STC19	3/8-24	3/16	3/16	18,8	167	13.9
STC20	1/4-28	1/8	1/8	5,4	48	4
STC25	10-32	3/32	3/32	2,3	21	1.6
STC26	1/4-28	1/8	1/8	5,4	48	4
STC27	8-36	5/64	5/64	1,4	12	1
STC30	6-40	1/16	1/16	0,7	6	.5
STC32	1/4-28	1/8	1/8	5,4	48	4
STC34	10-32	3/32	3/32	2,3	21	1.6
STC35	1/4-28	1/8	1/8	5,4	48	4
STC36	1/4-28	3/32	3/32	2,3	21	1.6
STCC-8	M8x1	9/64	9/64	11,8	105	8.8
STCC-9	M5x0,8	3/32	3/32	3,1	28	2.3
STCC-11	M6x1	1/8	1/8	5,1	45	3.8
STCC-20	M6x1	1/8	1/8	5,1	45	3.8
STCC-37	M8x1	3/32	3/32	11,8	105	8.8
STCC-38	M5x0,8	5/64	5/64	3,1	28	2.3
STCC-39	M10X1,25	1/8	1/8	35,0	206	25.9
STCC-40	M6x1	3/32	3/32	5,1	45	8