



KENLOC™

■ Зажимной штифт

Номер по каталогу	размер резьбы	верхний ключ шестигранник (мм)	нижний ключ шестигранник (мм)	Рекомендуемый крутящий момент		
				Нм	дюйм-фунт	фут-фунт
KLM23	M4 x 0,7	—	1,5	1,5	13	1.0
KLM33	M5 x 0,8	2,0	2,0	1,7	15	1.2
KLM33L	M5 x 0,8	2,0	2,0	1,7	15	1.2
KLM34	M5 x 0,8	2,0	2,0	1,7	15	1.2
KLM34L	M5 x 0,8	2,0	2,0	1,7	15	1.2
KLM43	M5 x 0,8	2,0	2,0	1,7	15	1.2
KLM44	M6,3 x 1	2,5	2,5	3,3	30	2.5
KLM46	M6,3 x 1	2,5	2,5	3,3	30	2.5
KLM46L	M6,3 x 1	2,5	2,5	3,3	30	2.5
KLM46S	M6,3 x 1	2,5	2,5	3,3	30	2.5
KLM54	M6,3 x 1	2,5	2,5	3,3	30	2.5
KLM56	M8 x 1	3,0	3,0	5,5	50	4.0
KLM58	M8 x 1	3,0	3,0	5,5	50	4.0
KLM58L	M8 x 1	3,0	3,0	5,5	50	4.0
KLM66	M10 x 1	4,0	4,0	8,0	70	5.6
KLM66L	M10 x 1	4,0	4,0	8,0	70	5.6
KLM68	M10 x 1	4,0	4,0	8,0	70	5.6
KLM68L	M10 x 1	4,0	4,0	8,0	70	5.6
KLM810	M12 x 1,25	4,0	4,0	9,0	80	6.4

■ Зажимной винт

Номер по каталогу	размер резьбы	верхний ключ шестигранник (мм)	нижний ключ шестигранник (мм)	Рекомендуемый крутящий момент		
				Нм	дюйм-фунт	фут-фунт
STCM4	M8 x 1	4,0	4,0	17,0	150	12.0
STCM5	M5 x 0,8	2,5	2,5	4,0	35	3.0
STCM8	M8 x 1	4,0	4,0	17,0	150	12.0
STCM	M5 x 0,8	2,5	2,5	4,0	35	3.0
9STCM11	M6 x 1	3,0	3,0	6,0	53	4.4
STCM19	M10 x 1,25	5,0	5,0	8,0	71	5.9
STCM20	M6 x 1	3,0	3,0	7,0	62	5.2
STCM24	M10 x 1,25	5,0	5,0	33,0	292	24.3
STCM25	M5 x 0,8	2,5	2,5	4,0	35	3.0
STCM26	M6 x 1	3,0	3,0	7,0	62	5.2
STCM27	M4 x 0,7	2,0	2,0	2,1	19	1.5
STCM32	M6 x 1	3,0	3,0	7,0	62	5.2
STCM35	M6 x 1	3,0	3,0	7,0	62	5.2
STCM37	M8 x 1	2,5	2,5	4,2	37	3.1
STCM38	M5 x 0,8	2,0	2,0	2,1	19	1.5
STCM39	M10 x 1,25	3,0	3,0	8,0	71	5.9
STCM40	M6 x 1	2,5	2,5	4,2	37	3.1